

POE Injector Technical Data Sheet



Sales Codes	Region	AC Plug Type
T0005669	North America, Central America, Japan, China	Type A & B
KITT0005671	Europe, South America, Asia, Africa	Type C & E/F
KITT0005670	United Kingdom, Ireland, Malaysia, Singapore, Arabian Peninsula	Type G
KITT0005673	Australia, New Zealand, China, Argentina	Type I
Specifications		
Description	Indoor Passive POE Injector compatible with all TEKTELIC Gateways	
AC Input Rating	100 - 240 Vac +/-10%, 50/60 Hz +/-3 Hz	
DC Output Rating	55Vdc, 1.1A up to 60W(max)	
POE	Supports IEEE802.3af/at/PoE++ devices	
Data Rate	10/100/1000 Mbps	
AC Connector	IEC 320 C6 receptacle (three wire) with 1.5m cord & plug	
Ethernet Connectors	Shielded RJ-45 data in, shielded RJ-45 data & power out	
Operating Environment	Indoor, IP40, 0°C to 40°C, 20% to 80% RH non-condensing, up to 5000m altitude	
Certifications	cUL/UL, CE, FCC CFR47 Part 15, EN55032, EN55035, IEC61000-4-2/3/4/5/6, IEC60068-2-6/27/32, RoHS, REACH, WEEE	
Efficiency	Level VI	
Protection	Over temperature, output overcurrent, overvoltage, short circuit permanent with no damage, auto-recovery	
LED Indicators	Input Power and PoE Load	
Dimensions (Injector Only)	145.51 x 65.8 x 33.5 mm	

