

# TEKTELIC SEAL EX

## ATEX Rated LoRaWAN® GPS Tracker for Personnel Safety

The **TEKTELIC SEAL** is a rugged, wearable **LoRaWAN®-connected GPS tracker** designed to ensure reliable location visibility and enhanced safety for personnel working remotely or in the field. Combining precise GNSS positioning with Bluetooth® Low Energy (BLE) support, SEAL enables near real-time outdoor tracking and continued location awareness indoors. With integrated safety features, extended battery life, and an IP67-rated enclosure with ATEX Zone 2 certification, SEAL delivers a scalable and dependable solution for workforce safety, monitoring, and operational efficiency across industrial and enterprise environments.



### Features

- » Up to **11 months of battery life\*** for long-term, maintenance-free wearable operation
- » **ATEX Zone 2 certified** for safe operation in hazardous and explosive environments
- » **Precise GNSS positioning** delivering accurate outdoor location tracking
- » **Integrated Bluetooth® Low Energy (BLE)** for continued tracking and proximity awareness indoors
- » User-activated **SOS / emergency** alert button with **audio and visual indication**
- » **Fall and impact detection** to enhance worker safety and emergency response
- » **Elevation detection** for multi-level location awareness
- » **Optional harness detection** to monitor proper equipment usage
- » **Rugged IP67-rated enclosure** suitable for harsh outdoor and industrial environments
- » **GNSS datalogging** for historical location analysis
- » **Compatible with standard LoRaWAN® gateways and network servers** for broad interoperability
- » **Quick and easy device onboarding & data viewing** using TEKTELIC LeapX™ mobile application
- » **TEKTELIC Kona Atlas™ support** for payload encoding and decoding
- » **Locus™ integration** for centralized device, data, and fleet management
- » **Rapid deployment** for scalable industrial asset-tracking applications

### Sensing Functions

- » GNSS
- » Accelerometer
- » Bluetooth Low-Energy (BLE) Transceiver
- » Pressure
- » Ambient Temperature (MCU Thermometer)
- » Battery Voltage Gauge



\*Actual battery life varies based on configuration, data rate, and operating temperature.

# TEKTELIC SEAL EX

## ATEX Rated LoRaWAN® GPS Tracker for Personnel Safety

### Technical and Functional System Specifications

| General System Parameters       |  |
|---------------------------------|--|
| Operational Temperature         | -20°C to 52°C  |
| Storage Temperature             | -25° to 55°C   |
| Operational Relative Humidity   | 5% - 95% Non-Condensing  |
| Ingress Protection              | IP67   |
| Size                            | 104 x 70 x 33.8 mm (Non-clip variant)  |
|                                 | 104 x 70 x 57.8 mm (Clip variant)  |
| Weight (without batteries)      | 100 g (add 15 g per battery)   |
| Battery                         | 3 x AA-cell LID  |
| Battery Life                    |  |
| Default Reporting Period* @SF7  | 7 months   |
| Default Reporting Period* @SF10 | 6 months   |
| Wireless Parameters (LoRa)      |  |
| RF Power (Max)                  | 15 dBm   |
| RF Sensitivity                  | -137 dBm (SF12, 125 kHz)   |
| Channel Plans                   | EU868, US915, AU915, AS923-1,-2,-3,-4, IN865, KR920  |
| Antenna                         | Internal   |
| LoRa Device Class               | Class A  |
| Specification Version           | 1.0.4  |
| Sensor Specifications           |  |
| GNSS Features                   | 2.5 m position accuracy** (CEP 50)   |
|                                 | Support of GPS/QZSS, GLONASS, Galileo, BeiDou  |
|                                 | GNSSs Data logging up to 3,000 entries   |
|                                 | Geofencing up to 4 circular geofences  |
|                                 | TTFF: 60 sec cold start, 5 sec hot start   |
| Accelerometer Sensitivity       | Sensitivity: -164 dBm tracking and navigation<br>-148 dBm cold start<br>-157 dBm hot start |
|                                 | Sample rate: 1, 10, 25, 50, 100, 200, 400 Hz   |
|                                 | Measurement range: +/-2, +/-4, +/-8, +/-16 g<br>Precision: 16, 32, 64, 192 mg              |
| BLE Sensitivity (0.1% BER)      | 125 kbps: -103 dBm<br>500 kbps: -98 dBm<br>2 Mbps: -91 dBm                                 |
| Certifications & Compliance     |  |
| Regulatory                      | FCC, ISED, CE (RED)  |
| Product Safety                  | IEC 62368-1  |
| Environmental                   | RoHS   |
| Certification                   | IECEX, ATEX Zone 2, UL / CSA   |

\*Default reporting behavior is: 1 geolocation report every 15 minutes in normal mode and every 1 minute in emergency state  
Emergency alarm status: every 15 minutes in normal state, every 1 minute in emergency state

TEKTELIC Communications is a premier supplier of best-in-class LoRaWAN® IoT Gateways, Sensors, and custom applications. These elements combined provide a powerful end-to-end solution that can be easily, quickly, and cost effectively deployed to address the most demanding IoT challenges.

For more information, please visit [www.tektelic.com](http://www.tektelic.com)

# TEKTELIC SEAL EX

## ATEX Rated LoRaWAN® GPS Tracker for Personnel Safety

*Barometric pressure: every 15 minutes in normal state, every 1 minute in emergency state*  
*\*\*Under open sky conditions*

---

TEKTELIC Communications is a premier supplier of best-in-class LoRaWAN® IoT Gateways, Sensors, and custom applications. These elements combined provide a powerful end-to-end solution that can be easily, quickly, and cost effectively deployed to address the most demanding IoT challenges.

For more information, please visit [www.tektelic.com](http://www.tektelic.com)