

PELICAN Ex Asset Tracker

LoRaWAN® and BLE Device for Outdoor Asset Tracking

TEKTELIC's PELICAN Ex is an ideal outdoor rated ATEX certified solution for locating, tracking, and managing assets in difficult RF environments where an explosive atmosphere may be present. The PELICAN Ex can be deployed as a tracker or a BLE Beacon for your asset tracking solutions.

- Industrial / Oil & Gas Sites
- Mining

- Hazardous Worker Safety
- **Processing Plants**



Technical and Functional System Specifications

General System Parameters

| Operational Temperature | -20°C to +50°C |
|-------------------------|---|
| Ingress Protection | IP67 |
| Size | 68 x 42 x 33 mm (excluding mounting features) |
| Battery | Lithium Thionyl Chloride C-cell |

Regulatory Compliance

| Safety | EN/IEC 62368-1 (CE) |
|--------|--------------------------------------|
| Radio | ETSI EN 300 220 |
| | ETSI EN 301-489-1/-3 |
| ATEX | EN IEC 60079-0 |
| | EN 60079-11 |
| | <ex> II 2G Ex ia IIC T4 Gb</ex> |
| | <ex> II 2D Ex ia IIIC T135°C Db</ex> |

LoRa Parameters

| RF Power | 15 dBm |
|-------------------|------------------------------|
| RF Sensitivity | up to -137dBm (SF12, 125kHz) |
| ISM Band | All Global ISM Bands |
| Antenna | Internal |
| LoRa Device Class | Class A |

Key Features

- Certified for ATEX Zone 1/21 locations
- 10 Year Battery Life Tracker Mode
- 3 Year Battery Life Beacon Mode
- Accelerometer
- Data Transmission via LoRaWAN® and BLE
- Internal Antennas
- All Global ISM Bands
- Small Form Factor for Diverse Deployments
- Bluetooth Low Energy Functionality
- Easily Integrated into LoRaWAN® Networks

BLE Beacon Parameters

| Tx Power | Up to 0 dBm |
|---------------|--|
| Battery life | 3 Year |
| BLE Protocols | iBeacon, Eddystone UID, Eddystone TLM |





+1.403.338.6900



WWW.TEKTELIC.COM