

# TEKTELIC TUNDRA Sensor

## LoRaWAN® Device for Cold Chain Environment Monitoring

TEKTELIC's TUNDRA Temperature Sensor with external probe is the ideal solution for maintaining optimal and consistent temperatures within cold rooms and refrigerated spaces. The device can be implemented within cold storage such as fridges, coolers, cold rooms and even freezers with minimal impact on battery life or radio signal strength. The Cold Room Temperature Sensor is seamlessly integrated with TEKTELIC's end-to-end IoT solution.

- Restaurants
- Supermarkets
- Food Service Cold Chain
- Medical Storage
- Pharmaceutical Storage
- Vaccine Storage

## Technical and Functional System Specifications

### General System Parameters

Operational Temperature	-40°C to 70°C
Ingress Protection	IP67
Size	67 x 43 x 36 mm
Battery	C Cell



### LoRa Parameters

RF Power	EU: 15 dBm    NA: 22dBm
RF Sensitivity	up to -137dBm (SF12, 125kHz)
ISM Band	All Global ISM Bands
Antenna	Internal
LoRa Device Class	Class A

### Regulatory Compliance

Safety	IEC 60950-1 (CE)
Regulatory	ETSI EN 300 220
	ETSI EN 301-489-1/-3
	FCC 15.247    FCC 15.209
	RSS-247    RSS-GEN

Specifications subject to change without notice.

### Key Features and Functions

- » -40° to +70°C Operability
- » External Temperature Probe
- » Door Open/Close Monitoring
- » 10 Year Battery Life
- » Internal Antenna
- » Small Form Factor for Diverse Deployments
- » 125 Days/3000 Entries of Stored Data
- » Ambient Temperature & Humidity Monitoring